


PRV

PATENT- OCH REGISTRERINGSVERKET
Patentavdelningen

PCT/E 03 / 0 1 0 7 0 #2



Intyg Certificate

Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.

(71) Sökande Mentorkraft, Lund SE
Applicant (s)

(21) Patentansökningsnummer 0202018-8
Patent application number

(86) Ingivningsdatum 2002-06-28
Date of filing

Stockholm, 2003-06-25

För Patent- och registreringsverket
For the Patent- and Registration Office


Sonia André

Avgift
Fee

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

PATENT- OCH
REGISTRERINGSVERKET
SWEDEN

Postadress/Adress
Box 5055
S-102 42 STOCKHOLM

Telefon/Phone
+46 8 782 25 00
Vx 08-782 25 00

Telex
17978
PATOREG S

Telefax
+46 8 666 02 86
08-666 02 86

BEST AVAILABLE COPY

APPLICANT:

STAFFAN GREBIUS

TITLE OF THE INVENTION

DEVICE FOR MIXING AND
DELIVERING BONE CEMENT

5

SUMMARY OF THE INVENTION

This invention relates to a device for mixing and
delivering pastes that require mixing prior to delivering,
10 and more particularly to a single use device that is able
to handle high viscosity pastes, like e.g. bone cement.

The device is of the type including means for mixing
and applying a paste such as bone cement or the like,
including a cylinder receiving the paste, a piston
15 reciprocable in the cylinder, a piston rod displaceable and
rotatable in the piston and forming mixing means for paste
received in the cylinder, and latch means for
interconnecting the piston and the piston rod to allow
displacement of the piston in the cylinder by means of the
20 piston rod for deposition of the paste outside the cylinder

BACKGROUND OF THE INVENTION

Bone cement is used e.g. in connection with surgical
replacement of a hip joint. Bone cement generally consists
25 of akrylate plastic, which is biocompatible. Depending on
the use, bone cement has got different viscosity
characteristics. For use in connection with hip joint
replacements, the viscosity is often quite high, whereas
the bone cement used for e.g. spinal disc enhancements has
30 lower viscosity. This invention mainly relates to mixing
and application of bone cements with higher viscosity, but
is just as useful for low viscosity applications.

For simplicity, the term bone cement will be used
throughout this application, although the invention can be
35 used for any other kind of paste that requires mixing prior
to application.

Presently, mixing of bone cement ingredients is mostly done in a separate vessel, whereupon the mixed bone cement is put into a bone cement applicator that generally is made of stainless steel. This method has some severe
5 drawbacks:

1. Mixing of the bone cement should preferably be performed under vacuum, since low ambient pressure reduces the presence of gas impurities in the bone cement, that leads to a connection with reduced
10 strength. The vacuum treatment is often performed after the components of the bone cement have been mixed. Applying the prior art method, the mixed (and vacuum treated) bone cement must be put into an applicator, which increases the risk of adding
15 gas impurities to the bone cement.
2. The applicator is usually not of single use type, which makes it necessary to disassemble the applicator to be able to clean it and sterilize it properly after it has been used. Additionally, the
20 applicator wears down by time.

The object of this invention is to provide a single use mixer/applicator in which the bone cement is mixed under vacuum and that is capable of handling bone cement with high viscosity.

25

BACKGROUND ART

US-A-5,951,160 discloses a bone cement applicator that uses the piston rod as the bone cement mixing means. After the mixing has been performed, the piston rod is
30 withdrawn towards the piston, whereupon two wings on the distal end of the piston rod are passed through a slot in the piston to be introduced into a cavity therein. Then, the rod is rotated slightly and the piston rod becomes secured to the piston by the wings received in the cavity.

This prior art device is simple, but has got some severe drawbacks:

1. It is not possible to use the device for high viscosity bone cement, since high viscosity bone cement will clog the slot in the piston and make it impossible to engage the wings on the piston rod with the piston.
2. The mixing cannot be performed under vacuum, since there are no withholding means for the piston that prevents the piston from being displaced in the cylinder by the force of the vacuum.
3. The mixing quality is poor, since there are only two wings on the end of the piston rod.

Additionally, the applicator according to US-A-5 951 160 is not provided with means facilitating the extrusion of bone cement from the cylinder, which means that the device must be put into some kind of device to facilitate the extrusion of the bone cement.

US-A-5,398,483 discloses a device and a method for application of bone cement, wherein the bone cement components are contained separated in a cartridge. When the bone cement is to be used, the sealing between the cartridge compartments is opened to allow the bone cement components to be mixed in the cartridge. After mixing the cartridge is placed in an applicator gun. This method has one large disadvantage: it is not possible to use any kind of additional components (like e.g. antibiotics), since the bone cement comes in a prepackaged, sealed cartridge.

Cem-Vac Inc. sell a combined device in which a piston for extruding the bone cement is located at one end of a cylinder and a piston for mixing the bone cement is located at the other end of the cylinder. The bone cement components are supplied to the cylinder through a hollow mixing piston rod. After the mixing is complete, the device

is placed in a pistol grip applicator, and the hollow piston rod is used as an applicator nozzle.

The prior art devices mentioned above use a separate pistol grip applicator for applying the required pressure
5 to the bone cement.

The present invention aims to overcome the abovementioned and other problems by providing a device in which the bone cement can be mixed under vacuum, which includes means for facilitating the application, and which
10 can be discarded after use.

SUMMARY OF THE INVENTION

The present invention provides a device for mixing and delivering bone cement of the kind referred to above,
15 which is characterised in that means are provided for locking the piston rod to the piston by jamming, said means allowing the piston rod to be locked to the piston at any position along the complete length of the piston rod.

Preferred details of the invention are defined in the
20 dependent claims.

INDUSTRIAL APPLICABILITY

As the population in the world's industrialised parts grow older, the need for different surgical corrections of
25 the shortcomings of the human body becomes more intense. For example, 15000 hip and knee joint replacements occur in Sweden only, every year. For most of these hip or knee joint replacements, bone cement is used for fastening the man-made hip or knee joint in the medullary canal of femur.

30 Since the speed at which the surgeon can work is important from a number of views, it is of importance to provide a device in which the bone cement can be mixed and from which the bone cement can be deposited. It is also of importance that the device can be discarded after use, so

that no personnel resources must be used for cleaning and disinfecting the device after use.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Fig. 1 and 2 are fragmentary axial cross sectional views of the proximal end portion of the device showing the interaction between the piston and the piston rod.

Fig. 3 is a fragmentary enlarged axial cross sectional view showing the interlocking between the piston
10 and the piston rod.

Fig. 4 is a cross sectional view taken along line A-A in fig 1.

Fig. 5 and 6 are fragmentary axial cross sectional views showing the interaction between the piston and an
15 external ring.

Fig. 7 a-e show five different operation steps of the device.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

20 Fig 1 shows a piston 1, a piston rod 2, a proximal end portion of a cylinder 3 and a part of a main housing 4. On the outside of the cylinder 3 an external ring 5, rotatable on the cylinder, is provided. The piston is divided into a front component 6 and a back component 7,
25 which engage each other at plane surfaces. In each of the piston components 6, 7 there is provided in plane surface, a recess 8,9, respectively, which recesses 8,9 are placed at an angle with respect to each other, as shown in fig 4. A lock member 10 with a central opening through which the
30 piston rod 2 is displaceably received is located in recess 9 and is biased by a helical pressure spring 11, housed in a recess 11b in the back component 7 of the piston 1, to rest upon the surface of the front component 6 of the piston 1.

The front component 6 of the piston 1 is provided with sealing means 12,13, which seal the connections piston 1/cylinder 3 and piston 1/piston rod 2.

Ring securing means 14 are provided to prevent the
5 ring 5 from being rotated. The ring securing means 14 is biased by a helical pressure spring 15, which rests upon an abutment 15b in the housing 4. Behind the piston 1, an elastic body 16 is provided, that rests between a tubular boss 16b formed by the housing, and the back component 7 of
10 the piston 1. The piston rod 2 is slidable through all components of the piston 1.

Two pins 17,18 are provided to prevent the front component 6 of the piston 1 from rotating by being firmly attached to the front component 6 of the piston 1, and run
15 in two holes 17b, 18b provided in the main housing 4. Except from serving as means preventing the front component 6 of the piston 1 from rotating, the pins 16, 17 also serve to hold the piston components 6,7 together. The back component 7 of the piston 1 is provided with two slots 23,
20 23b (see fig 4), formed to allow the back component 7 to rotate with respect to the front component 6.

On the front end of the piston rod 2 mixing means 21 are provided. The mixing means 21 act to mix the constituents of the paste housed in the cylinder 3 upon
25 reciprocal movement and rotation of the piston rod 2, and may be in form of several radial wings extending from the distal end of the piston rod 2.

In fig. 2, the piston 1 has been pulled backwards by force applied to the piston rod 2, compressing the elastic
30 body 16, the ring securing means 14 being lifted from recesses 22 in the external ring 5, which makes it possible to rotate the external ring 5. Since the external ring 5 is connected to the back component 7 of the piston 1 by means of small pins 24,25 (shown in fig 5), the back component 7
35 will rotate as well, which is allowed by the design of

slots 23 (shown in fig 4). As the back component 7 of the piston 1 is rotated by rotating the external ring 5, and the front component 6 is held against rotation by the pins 16, 17, the recesses 8,9 will overlap. This leads to the lock member 10 falling down into the recess 8 in the front component 6 of the piston 1. The lock member 10 falling down into the recess 8 irreversibly locks the piston 1 to the piston rod 2 in the forward direction. It is however possible to let the piston 1 slide along the piston rod 2 towards the proximal end of the device. As will be explained below, this is advantageous in some aspects.

The locking action between the lock member 10 and the piston rod 2 is shown in figure 3, which shows the lock member 10 interacting with the recess 8 in the front component 6 of the piston 1. Since the lock member 10 is supported on only one side, laterally displaced from the centre axis of the piston rod 2, the lock member 10 jams the piston rod 1 in the forward direction.

Fig. 4 shows the lock member 10 in its recess 9 in the back component 7 of the piston 1 before it has fallen down into the recess 8 in the front component 6 of the piston 1. Also shown is (dashed) the contour of the recess 8 in the front component 6 of the piston 1. Furthermore, the position of the two pins 17, 18 and their corresponding slots 23 in the back component 7 of the piston 1 are shown. The two small pins 24 and 25 connect the external ring 5 with the back component 7 of the piston 1.

As the piston 1 is locked to the piston rod 2, the extrusion of paste from the cylinder 3 can be started by starting to move the piston 1 forward by means of the piston rod 2. As the piston 1 moves forward, the connection between the piston 1 and the main housing 4 by the pins 16,17 releases, just as the connection between the external ring 5 and the back component 7 of the piston 1.

Fig 5 shows an example of how the interaction between the external ring 5 and the back component 7 of the piston 1 can be designed. The two small pins 24, 25 are received in two open slits, one of which is shown at 26, in the back component 7 of the piston 1. The two slits are open to allow forward motion of the piston 1.

Two open slits, one of which is shown in fig 6 at 26, are provided each with a restriction, one of which is shown at 28. The restrictions serve to restrict forward motion of the piston 1 without applying a substantial force to the piston 1. They also serve to give a distinct click as the piston 1 commences its travel forward to extrude the paste housed in the cylinder 3, and thereby tells the user that the unit is ready for applying the paste.

All details mentioned above are housed in the main housing 4 including pressing means 19 and locking means 20 that act on the piston rod 2. The pressing means 19 are biased by a helical pressure spring 19b, one end of which acts on the tubular boss 16b, the other end on the pressing means 19. The helical pressure spring 19b serves to press the pressing means 19 towards the proximal end of the device. The locking means 20 are spring loaded by a helical pressure spring 20b, which presses the locking means 20 backwards. The locking means 20 can be deactivated by being pressed towards the projection 20c. Both the pressing means 19 and the locking means 20 are actuated by a bar 19c, that in turn is connected to some kind of power grip, e.g. a pistol grip.

The function of the pressing 19 and locking means 20 is as follows: When the power grip is actuated, the bar 19c will travel forward (in the direction of the arrow shown in fig 1), activating the locking means 20 by releasing said means from the projection 20c, biased by the helical pressure spring 20b. Simultaneously, the bar 19c acts on the pressing means 19, which leads to a jamming effect

between the pressing means 19 and the piston rod 2, pressing the piston rod 2 forward under compression of the helical pressure spring 19b. During the forward moving procedure of the piston rod 2, the locking means slide
5 along the piston rod 2.

As the power grip is released, the jamming effect between the pressing means 19 and the piston rod 2 discontinues, which leads to the helical pressure spring 19b pressing the pressing means 19 back along the piston
10 rod 2. If the power grip is totally released, the bar 19c will remove the jamming action between the locking means 20 and the piston rod 2 by forcing (the force emanating from helical pressure spring 19d) the locking means 20 towards the projection 20c.

15 In the position where the power grip is totally released, the piston rod 2 is not in any way restricted from being pushed and pulled back and forth (or being rotated) through the components in the main housing, allowing mixing of the paste constituents

20 In the following, the function of the device will be described, with reference to the components mentioned above, and to fig. 7.

In the first step, the components of the paste that is to be mixed and applied are introduced into the cylinder
25 3. After the paste components have been received in the cylinder 3, the cylinder 3 is connected to a vacuum source P, that reduces the presence of gases in the paste, both such gases that emanate from air being mixed into the paste and gases that are formed as a result from the curing
30 process of the paste.

By pushing and pulling the piston rod 2 back and forth and rotating it, the mixing means 21 on the distal end of the piston rod 2 mixes the components of the paste. These operational steps are shown in figs. 7a and b.

The next sequential step is to lock the piston rod 2 to the piston 1. This is accomplished by pulling the piston rod 2 forcefully backwards and simultaneously turning the external ring 5, as shown in fig 7c.

5 In figure 7d, the power grip is actuated, leading to the piston being pushed forward, whereby the paste fills out any empty spaces in the cylinder 3, as the vacuum source P is still connected to the cylinder.

10 In fig 7d, the vacuum source P is disconnected from the cylinder 3 and a nozzle is attached to the front end of the cylinder 3. The nozzle can have different configurations depending on what kind of application the device should be used for.

15 If the piston rod 2 would slip forward without taking the piston 1 forward and hence not extrude any paste, the piston rod 2 can be retracted and the extrusion of paste can be recommenced.

20 One very important feature of the function of the device is that it is not necessary that the piston rod 2 is completely withdrawn towards the piston 1 to be able to lock the piston 1 to the piston rod 2, as is the case with the prior art device described in US-A-5,951,160. If enough force is applied to the piston 1, it is possible to turn the external ring 5 and hence lock the piston 1 to the
25 piston rod 2. This feature is very important, since it makes it possible to lock the piston 1 to the piston rod 2 even if high viscosity paste would make it too hard to pull the piston rod 2 so far that the mixing means 21 comes in physical contact with the piston 1.

30 One further advantage with the embodiment in which a lock member 10 is falling down into a recess 8 is that it irreversibly locks the piston 1 to the piston rod 2, which prevents the unit from being used more than once.

CLAIMS

1 Device for mixing and applying a paste such as bone cement or the like, including a cylinder (3) receiving the paste, a piston (1) reciprocable in the cylinder (3), a
5 piston rod (2) displaceable and rotatable in the piston (1) and forming mixing means (21) for paste received in the cylinder 3, and latch means for interconnecting the piston (1) and the piston rod (2) to allow displacement of the piston (1) in the cylinder (3) by means of the piston rod
10 (2) for deposition of the paste outside the cylinder (2), characterized in that means are provided for locking the piston rod (2) to the piston (1) by jamming, said means allowing the piston rod (2) to be locked to the piston (1) at any position along the complete length of the piston rod
15 (2).

2 Device according to claim 1, characterized in that the device is a single use device.

3 Device according to claim 1, characterized in that the piston is divided into front (6) and back (7)
20 components rotatable relative one another.

4 Device according to claim 1, characterized in that the cylinder (3) is gas tight, which enables mixing of the paste under vacuum.

5 Device according to claim 1, characterized in that
25 the jamming means in the piston (1) include a lock member (10) with a central hole receiving the piston rod, which member (10) in the jamming position is supported in a position laterally displaced relative to the centre axis of the piston rod (2).

6 Device according to claim 1, characterized in that
30 an external ring (5) or the like on the cylinder is rotatable for locking of the piston (1) to the piston rod (2).

7 Device according to claim 6, characterized in that
35 the external ring (5) or the like is secured by securing

means (14), to prevent the ring (5) from being turned accidentally.

8 Device according to claim 6, characterized in that the piston rod (2) is restricted from being pulled
5 backwards by an elastic body (16) provided behind the piston (1).

9 Device according to claim 1, characterized in that the piston (1) is provided with sealing means (12, 13) to ensure the gastightness of the cylinder (3).

10 10 Device according to claim 1, characterized in that single use is guaranteed by irreversibly locking the piston (1) to the piston rod (2).

020626 MB

ABSTRACT


Device for mixing and applying a paste such as bone cement or the like, including a cylinder 3 receiving the paste, a piston 1 reciprocable in the cylinder 3, a piston
5 rod 2 displaceable and rotatable in the piston 1 and forming mixing means 21 for paste received in the cylinder 3, and latch means for interconnecting the piston 1 and the piston rod 2 to allow displacement of the piston 1 in the
10 cylinder 3 by means of the piston rod 2 for deposition of the paste outside the cylinder 2, characterized in that means are provided for locking the piston rod 2 to the piston 1 by jamming, said means allowing the piston rod 2 to be locked to the piston 1 at any position along the complete length of the piston rod 2.

9
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179

0000018-8

Fig 1


IPV 02-0-28 M



0000019-8

Fig 2


PRV 02-00-28 M




0000018-8

Fig 3

PRV 02-0-28 M





01000000

Fig 5




Fig 6





Fig 7



0000010000

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.